

PRODUCT DATASHEET

Mini CX

FASTCAM series by Photron



FASTCAM Mini CX

Megapixel CMOS Sensor:

1920 x 1400 pixels at 750fps
1920 x 1080 pixels at 1,000fps
1280 x 800 pixels at 2,000fps
1280 x 256 pixels at 5,000fps

Class Leading Light Sensitivity:

ISO 5,000 color
ISO 10,000 monochrome

Global Electronic Shutter:

4µs independent of frame rate

Dynamic Range (ADC):

30-bit color
10-bit monochrome

Compact and Lightweight:

75mm (H) x 75mm (W) x 123.5mm (D)
2.95" (H) x 2.95" (W) x 4.86" (D)
Weight: 1.2Kg (2.6lbs.)

Internal Recording Memory:

8GB

Fast Gigabit Ethernet Interface:

Provides high-speed image download to standard notebook/PC

Video Out:

HDMI Video Output

WiFi Connection:

Live view and camera set-up via wireless network (2.4GHz/5GHz, 802.11a/g/n).

Removable Data Storage:

CFast Compact Flash drive for high-speed data transfer. Auto download to CFast media after recording is available.

High-G Rated:

Suitable for application in high-G environments; Operation tested to 150G, 11ms, 6-axes, 50 times

Built-in Battery:

Provides memory backup as well as 30 minutes of operational power.

COMPACT HIGH-SPEED CAMERA WITH HD IMAGE RESOLUTION

Ideally suited for both on-board and off-board vehicle safety testing, the Mini CX delivers an exceptional combination of resolution, frame rate, light sensitivity and durability in a compact, stand-alone package.

With 1080 HD resolution at 1,000 frame per second and an industry leading light sensitivity of ISO 5,000 color and ISO 10,000 monochrome, the Mini CX provides outstanding image quality. Designed for the space limited locations and High-G operating environments common to automotive safety testing as well as certain military/defense applications, the Mini CX is Photron's smallest, lightest and – with operational testing to 150G – most rugged camera.

Additional features add to the usability of the Mini CX. For instance, HDMI video output allows easy local focusing of the camera. An internal battery offers 30 minutes of camera operation if the primary power source fails during a test. Rapid download to nonvolatile memory ensures protection for recorded images. A built-in accelerometer provides a backup trigger source.





1" C-mount Compatible Image Sensor:

The Mini CX uses an advanced CMOS image sensor that has been optimized for high light sensitivity and image quality.

A 6.6 micron pixel pitch provides a full resolution image sensor size of 12.7 x 7.12mm, with a diagonal of 14.6mm.

The Mini CX is compatible with lenses designed for both 1" C-mount and FX/DX SLR (with adapter) formats with no vignetting.

Junction Box Compatibility:

The Mini CX is compatible with Photron's on-board high-G Junction Box for easy multi-camera workflow.

Camera Performance Specifications

Model	Mini CX
Full Frame Performance	750fps 1920 x 1400 pixels
Example Frame Rates	1,000fps 1920 x 1080 pixels
	1280 x 800 pixels
	5,000fps 1280 x 256 pixels
Minimum Exposure Time	Global electronic shutter to 4µs selectable independent of frame rate
Dynamic Range (ADC)	10-bit monochrome 30-bit color
Memory Capacity	8GB
Sensor Size / Pixel Size	12.7 x 7.12mm (diagonal 14.6mm), 1-inch C-mount compatible
Built-in Battery	Operational power up to 30 minutes and memory back-up
Input / Output	Input: Trigger (TTL/Switch), sync, ready, event Output: trigger, sync, ready, rec, exposure
Camera Control Interface	High-speed Gigabit Ethernet / Wifi
Video Out	HDMI
Data Storage Media	Removable CFast flash memory with auto download function
Supported OS	Microsoft Windows operating systems including: 7, 8, 8.1, 10, 11 (32/64-bit)

Mechanical and Environmental Specifications

Mechanical	
Lens Mount	C-mount provided
External Dimensions	
Camera Body (excluding protrusions)	75mm (H) x 75mm (W) x 123mm (D) 2.95" (H) x 2.95" (W) x 4.86" (D)
Weight	
Camera Body	1.2kg (2.6lbs)
Environmental	
Operating Temperature	0 to 40C, 32° to 104°F
Storage Temperature	-20 to 60C, -4° to 140°F
Humidity	85% or less (non-condensing)
Operational Shock	150G, 11ms, 6-axes, 50 times

PHOTRON USA, INC.
9520 Padgett Street, Suite 110
San Diego, CA 92126
USA

Tel: 858.684.3555 or 800.585.2129
Fax: 858.684.3558
Email: image@photron.com
www.photron.com

PHOTRON EUROPE LIMITED
The Barn, Bottom Road
West Wycombe
Bucks. HP14 4BS
United Kingdom

Tel: +44 (0) 1494 481011
Fax: +44 (0) 1494 487011
Email: image@photron.com
www.photron.com

PHOTRON (Shanghai)
Room 20C, Zhao-Feng
World Trade Building
No. 369, JiangSu Road
Chang Ning District
Shanghai, 200050 China
Tel: +86 (21) 5268-3700
Fax: +86 (21) 5268-3702
Email: info@photron.cn.com
www.photron.cn.com

PHOTRON LIMITED
21F, Jinbocho Mitsui Bldg.
1-105 Kanda Jimbocho
Chiyoda-ku, Tokyo 101-0051
Japan

Tel: +81 (3) 3518-6271
Fax: +81 (3) 3 3518-6279
Email: image@photron.co.jp
www.photron.co.jp